


### PAGBA40-PP-AS

Linear plain bearing and housing unit

Linear plain bearing and housing unit; sealed on all sides, with relubrication facility

## Technical information



### Your current product variant

Size code	40
Seal	PP
Relubrication facility	AS

### Main Dimensions & Performance Data

F <sub>w</sub>	40 mm	Diameter of ball complement
H	87 mm	Height
L	80 mm	Length
Tol L	h12	Tolerance
B	108 mm	Width
≈m	1,09 kg	Weight



### Mounting dimensions

J <sub>B</sub>	86 mm	
Tol J <sub>B</sub>	+ 0,2 mm	Upper tolerance
Tol J <sub>B</sub>	- 0,2 mm	Lower tolerance
A <sub>5</sub>	54 mm	
Tol A <sub>5</sub>	+ 0,015 mm	Upper tolerance
Tol A <sub>5</sub>	- 0,015 mm	Lower tolerance
L <sub>4</sub>	78 mm	
L <sub>5</sub>	56 mm	
J <sub>L</sub>	58 mm	
Tol J <sub>L</sub>	+ 0,2 mm	Upper tolerance
Tol J <sub>L</sub>	- 0,2 mm	Lower tolerance
H <sub>2</sub>	45 mm	Center height
Tol H <sub>2</sub>	+ 0,01 mm	Upper tolerance
Tol H <sub>2</sub>	- 0,01 mm	Lower tolerance
A <sub>3</sub>	30 mm	
H <sub>6</sub>	11 mm	
Tol H <sub>6</sub>	- 0,5 mm	Tolerance
N <sub>1</sub>	9,2 mm	
N <sub>3</sub>	15 mm	
K <sub>5</sub>	M8	
K <sub>8</sub>	NIPA2	Lubrication nipple