
**PAGBA50-PP-AS**

Linear plain bearing and housing unit

Linear plain bearing and housing unit; sealed on all sides, with relubrication facility

## Technical information

**Your current product variant**

Size Code	50
Seal	PP
Relubrication facility	AS

**Main Dimensions & Performance Data**

F <sub>W</sub>	50 mm	Diameter of ball complement
H	98 mm	Height
L	100 mm	Length
Tol L	h12	Tolerance
B	130 mm	Width
≈m	1,65 kg	Weight



### Mounting dimensions

J <sub>B</sub>	108 mm	
Tol J <sub>B</sub>	+ 0,2 mm	Upper tolerance
Tol J <sub>B</sub>	- 0,2 mm	Lower tolerance
A <sub>5</sub>	65 mm	
Tol A <sub>5</sub>	+ 0,015 mm	Upper tolerance
Tol A <sub>5</sub>	- 0,015 mm	Lower tolerance
L <sub>4</sub>	70 mm	
L <sub>5</sub>	72 mm	
J <sub>L</sub>	50 mm	
Tol J <sub>L</sub>	+ 0,2 mm	Upper tolerance
Tol J <sub>L</sub>	- 0,2 mm	Lower tolerance
H <sub>2</sub>	50 mm	Center height
Tol H <sub>2</sub>	+ 0,015 mm	Upper tolerance
Tol H <sub>2</sub>	- 0,015 mm	Lower tolerance
A <sub>3</sub>	34 mm	
H <sub>6</sub>	12,5 mm	
Tol H <sub>6</sub>	- 0,5 mm	Tolerance
N <sub>1</sub>	9,2 mm	
N <sub>3</sub>	15 mm	
K <sub>5</sub>	M8	
K <sub>8</sub>	NIPA2	Lubrication nipple