



### BKE.TSX65-D-SO [↗](#)

#### Braking/clamping element

Braking and clamping element BKE.TSX..-D, hydraulic connector on top face, for linear recirculating roller bearing and guideway assembly

## Technical information



### Your current product variant

Oil feed	SO	Oil feed from above
----------	----	---------------------

### Main Dimensions & Performance Data

H	90 mm	Height sytem
	without	Adapter plate
B	125 mm	Width of braking and clamping element
L	186 mm	Length braking and clamping element
	11.000 N	Clamping force
≈m	12,66 kg	Weight



### Dimensions

J <sub>B</sub>	96 mm	Hole pattern
J <sub>C</sub>	96 mm	Hole pattern
A <sub>1</sub>	22 mm	Distance
J <sub>L</sub>	150 mm	Hole pattern
C <sub>7</sub>	0 mm	Distance
H <sub>1</sub>	18,2 mm	Space (system)
H <sub>3</sub>	17,5 mm	Mounting dimension
A <sub>L2</sub>	7,5 mm	Distance
d <sub>1</sub>	M16x1,5	Size thread
SO	16x2	O-ring
	15 mm	Max. diameter of the oil feed hole
G <sub>2</sub>	M14	Size thread above for DIN ISO 4762-12.9
M <sub>A</sub>	229 Nm	Tightening torque above