



### BKE.TKVD25-SO

#### Braking/clamping element

Braking and clamping element BKE.TKVD..-SO, hydraulic connector on top face, for four-row linear recirculating ball bearing and guideway assembly

## Technical information



### Your current product variant

Size Code	25
Oil feed	SO Oil feed from above

### Main Dimensions & Performance Data

H	47 mm	Height system
	without	Adapter plate
B	47 mm	Width of braking and clamping element
L	91 mm	Length braking and clamping element
	1.000 N	Clamping force
≈m	0,9 kg	Weight



### Dimensions

J <sub>B</sub>	38 mm	Hole pattern
J <sub>C</sub>	34 mm	Hole pattern
A <sub>1</sub>	10 mm	Distance
J <sub>L</sub>	75 mm	Hole pattern
C <sub>7</sub>	0 mm	Distance
H <sub>1</sub>	6,5 mm	Space (system)
H <sub>3</sub>	6 mm	Mounting dimension
A <sub>L2</sub>	5 mm	Distance
d <sub>1</sub>	M6x1	Size thread
SO	7x1,5	O-ring
	6 mm	Max. diameter of the oil feed hole
G <sub>2</sub>	M6	Size thread above for DIN ISO 4762-12.9
M <sub>A</sub>	17,4 Nm	Tightening torque above