



IMAGE  
COMING SOON





## RUKS45-D-A-H-SO

### Braking/clamping element

Clamping element RUKS...-D-A-H-SO, for linear recirculating roller bearing and guideway assembly, oil connector on top

## Technical information




### Your current product variant

Size code	45	
Version	D	
Internal design	A	
Carriage design	H	High carriage
Oil feed	SO	Oil feed from above

### Main Dimensions & Performance Data

H	70 mm	Height system
B	84 mm	Width clamping element
L	156,6 mm	Length of clamping element
≈m	4,25 kg	Weight



### Mounting dimensions

J <sub>B</sub>	60 mm	Hole pattern width
L <sub>1</sub>	134 mm	Length saddle plate
J <sub>L1</sub>	60 mm	Hole pattern lengthwise
J <sub>L5</sub>	43,5 mm	Distance
N <sub>2 max</sub>	6 mm	Max diameter lubrication hole adjacent constr
H <sub>1</sub>	8,7 mm	Space (system)
H <sub>3</sub>	58,3 mm	
T <sub>7</sub>	12,5 mm	Depth thread
G <sub>2</sub>	M10	Size thread above for DIN ISO 4762-12.9
M G <sub>2</sub>	83 Nm	Tightening torque above

### Related products

TSX45-E; TSX45-F	Suitable guideway
RUE45-E; RUE45-F	Suitable system