

**FAG****LOE232-N-AL-L**

## Plummer block housing

Plummer block housing, split, for spherical roller bearings, oil-lubrication



## Technical information

**Main Dimensions & Performance Data**

|                |        |                |
|----------------|--------|----------------|
| d              | 160 mm | Shaft diameter |
| a              | 660 mm | Length base    |
| h <sub>1</sub> | 400 mm | Height         |
| g <sub>1</sub> | 290 mm | Total width    |
| ≈m             | 136 kg | Weight         |

**Dimensions**

|                |        |                          |
|----------------|--------|--------------------------|
| b              | 200 mm | Width base               |
| c              | 70 mm  | Height base              |
| D              | 290 mm | Outside diameter bearing |
| d <sub>2</sub> | 170 mm | Shaft diameter shoulder  |
| d <sub>5</sub> | M160X3 | Thread shaft nut         |
| g              | 210 mm | Width housing body       |
| g <sub>3</sub> | 20 mm  | Wall thickness           |
| h              | 220 mm | Center height            |
| m              | 530 mm | Distance fixing bore     |
| n              | 110 mm | Bore distance width      |
| s              | M36    | Size of fixing screws    |
| u              | 42 mm  | Width slot               |
| v              | 60 mm  | Length slot              |
| w              | 80 mm  | Location collar width    |





### Additional information

|       |                            |
|-------|----------------------------|
| 4,7 l | Oil quantity first filling |
| 80 mm | Maximum height oil level   |
| 60 mm | Minimum height oil level   |

### Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -20 °C | Operating temperature min. |
| T <sub>max</sub> | 100 °C | Operating temperature max. |