

**FAG****32219-DY**

Tapered roller bearing

Tapered roller bearings 322, main dimensions  
acc. to DIN 720, separable

## Technical information

## Your current product variant

Tolerance class	PN	Normal (ISO 492:2014)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Internal design	Standard	
Quality level	Standard	
Number of rows	1	Single-row design

## Main Dimensions &amp; Performance Data

d	95 mm	Bore diameter
D	170 mm	Outside diameter
B	43 mm	Width, inner ring
C	37 mm	Width, outer ring
T	45,5 mm	Width, total
$C_r$	275.000 N	Basic dynamic load rating, radial
$C_{0r}$	375.000 N	Basic static load rating, radial
$C_{ur}$	44.000 N	Fatigue load limit, radial
$n_G$	4.150 1/min	Limiting speed
$n_{gr}$	2.800 1/min	Thermal speed rating
$\approx m$	4.000 g	Weight





### Mounting dimensions

$d_{a \max}$	108 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	107 mm	Minimum diameter of shaft shoulder
$D_{a \min}$	145 mm	Minimum diameter of housing shoulder
$D_{a \max}$	158 mm	Maximum diameter of housing shoulder
$D_{b \min}$	161 mm	Minimum diameter of housing shoulder
$C_{a \min}$	5 mm	Minimum axial space
$C_{b \min}$	8,5 mm	Minimum axial space
$r_{a \max}$	3 mm	Maximum fillet radius of shaft
$r_{b \max}$	2,5 mm	Maximum fillet radius of housing

### Dimensions

$r_{1, 2 \min}$	3 mm	Minimum chamfer dimension of inner ring back face
$r_{3, 4 \min}$	2,5 mm	Minimum chamfer dimension of outer ring back face
$a$	39 mm	Distance between the apexes of the pressure cones
$d_1$	129,3 mm	Guidance rib diameter of inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Calculation factors

$e$	0,42	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y$	1,43	Dynamic axial load factor
$Y_0$	0,79	Static axial load factor

### Additional information

T3FC095

Comparative designation to ISO 10317 and ISO 355



### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed