

**FAG****HC6210-2Z-L038-C3**

Deep groove ball bearing

Deep groove ball bearing HC63...-2Z, Hybrid bearing, single row, shields, steel sheet metal cage

## Technical information



## Your current product variant

Material Bearing	HC	Hybrid bearing, rolling elements ceramic, bearing rings made of steel
Type of seal	2Z	Non-contact shield on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	L038	Grease (L038/customer specific)
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	50 mm	Bore diameter
D	90 mm	Outside diameter
B	20 mm	Width
C <sub>r</sub>	43.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	27.000 N	Basic static load rating, radial
C <sub>ur</sub>	1.070 N	Fatigue load limit, radial
n <sub>G</sub>	10.800 1/min	Limiting speed
n <sub>gr</sub>	9.100 1/min	Reference speed
m	0,463 kg	Weight



### Mounting dimensions

$d_{a \min}$	57 mm	Minimum diameter shaft shoulder
$D_{a \max}$	83 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	1,1 mm	Minimum chamfer dimension
$D_1$	77,92 mm	Shoulder diameter outer ring
$D_2$	80,04 mm	Caliber diameter outer ring
$d_1$	62 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Calculation factors

$f_0$	16	Calculation factor
-------	----	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides
	Current insulated