

**FAG****6326-2Z-L038-C3**

Deep groove ball bearing

Deep groove ball bearing 63...-2Z, single row, shields, steel sheet metal cage

## Technical information



## Your current product variant

Sealing	2Z	Non-contact shield on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	L038	Grease (L038/customer specific)
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	130 mm	Bore diameter
D	280 mm	Outside diameter
B	58 mm	Width
$C_r$	244.000 N	Basic dynamic load rating, radial
$C_{0r}$	214.000 N	Basic static load rating, radial
$C_{ur}$	10.100 N	Fatigue load limit, radial
$n_G$	2.700 1/min	Limiting speed
$n_{gr}$	3.500 1/min	Reference speed
$\approx m$	15,5 kg	Weight



### Mounting dimensions

$d_{a \min}$	147 mm	Minimum diameter shaft shoulder
$D_{a \max}$	263 mm	Maximum diameter of housing shoulder
$r_{a \max}$	3 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	4 mm	Minimum chamfer dimension
$D_1$	231,25 mm	Shoulder diameter outer ring
$D_2$	236,85 mm	Caliber diameter outer ring
$d_1$	178,4 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	160 °C	Operating temperature max.

### Calculation factors

$f_0$	13,5	Calculation factor
-------	------	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides