



FAG

NJ2218-E-XL-TVP2>A

Cylindrical roller bearing

Cylindrical roller bearing NJ..-E-XL-TVP2,
with cage, single row, semi-locating bearing,
2 ribs on outer ring, 1 rib on inner ring, type
NJ

X-life

Technical information






Your current product variant

Design	E	Increased Capacity Design
Cage	TVP2	Solid Window Cage made from PA66
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	90 mm	Bore diameter
D	160 mm	Outside diameter
B	40 mm	Width
C _r	285.000 N	Basic dynamic load rating, radial
C _{0r}	315.000 N	Basic static load rating, radial
C _{ur}	56.000 N	Fatigue load limit, radial
n _G	6.000 1/min	Limiting speed
n _{gr}	3.250 1/min	Reference speed
m	3,19 kg	Weight





Mounting dimensions

$d_{a \min}$	101 mm	Minimum diameter shaft shoulder
$d_{a \max}$	105 mm	Maximum diameter of shaft shoulder
$D_{a \max}$	149 mm	Maximum diameter of housing shoulder
$d_{c \min}$	116 mm	Minimum shaft shoulder

$r_{a \max}$	2 mm	Maximum recess radius
--------------	------	-----------------------

Dimensions

r_{\min}	2 mm	Minimum chamfer dimension
$r_{1 \min}$	2 mm	Minimum chamfer dimension
s	2,5 mm	Axial displacement
E	145 mm	Raceway diameter outer ring
F	107 mm	Raceway diameter inner ring
$D_{1 \min}$	139,7 mm	Minimum rib diameter outer ring
d_1	114,3 mm	Maximum rib diameter inner ring

Temperature range


T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Additional information


HJ2218-E

L-washer

Characteristics



Radial load



Axial load in one direction



Grease Lubrication



Oil Lubrication



Not sealed