

**PUMP700-2L**

Hydraulic pump, manual

Hand pump, two-stage

Technical information

Your current product variant

| | | |
|---------|------|-----------------------------|
| Series | PUMP | Series PUMP |
| Version | HN | For use with hydraulic nuts |

Technical data

| | | |
|----------------|--------------------------------|---|
| P_{max} | 700 bar | Maximum operating pressure |
| p_1 | 20 bar | Operating pressure, 1st stage |
| \dot{V}_{H1} | 12,9 cm ³ | Oil flow/stroke, 1st stage |
| \dot{V}_{H2} | 2,3 cm ³ | Oil flow/stroke, 2nd stage |
| V_{max} | 2 l | Volume of oil container |
| V_{eff} | 1,6 l | Useable oil quantity |
| η_{40} | 32 – 46 mm ² /s | Oil viscosity in accordance with ISO VG at 40°C |
| L_0 | 1.500 mm | Hose length |
| | Quick coupling G $\frac{1}{4}$ | Coupling |
| | 620 mm | Length pump |
| | 150 mm | Width pump |
| | 170 mm | Height pump |
| m | 6 kg | Weight |

Additional information

preferably in combination with hydraulic nuts HYDNUT

Use



View product details on medias

13.06.2026, 19:40:45 UTC

SCHAEFFLER

Related products

HYDNUT.-E
HYDNUT.-E-INCH
HYDNUT.-HEAVY