

**PUMP700-2L**

Hydraulic pump, manual

Hand pump, two-stage

## Technical information

**Your current product variant**

Series	PUMP	Series PUMP
Version	HN	For use with hydraulic nuts

**Technical data**

$P_{max}$	700 bar	Maximum operating pressure
$p_1$	20 bar	Operating pressure, 1st stage
$\dot{V}_{H1}$	12,9 cm <sup>3</sup>	Oil flow/stroke, 1st stage
$\dot{V}_{H2}$	2,3 cm <sup>3</sup>	Oil flow/stroke, 2nd stage
$V_{max}$	2 l	Volume of oil container
$V_{eff}$	1,6 l	Useable oil quantity
$\eta_{40}$	32 – 46 mm <sup>2</sup> /s	Oil viscosity in accordance with ISO VG at 40°C
$L_0$	1.500 mm	Hose length
	Quick coupling G $\frac{1}{4}$	Coupling
	620 mm	Length pump
	150 mm	Width pump
	170 mm	Height pump
$m$	6 kg	Weight

**Additional information**

preferably in combination with hydraulic nuts HYDNUT

Use



View product details on medias

13.06.2026, 18:27:45 UTC

**SCHAEFFLER**

### Related products

---

HYDNUT.-E  
HYDNUT.-E-INCH  
HYDNUT.-HEAVY