



FAG

NJ230-E-XL-MPAX-C3 [↗](#)

Cylindrical roller bearing

Cylindrical roller bearing NJ..-E-XL-MPAX,
with cage, single row, semi-locating bearing,
2 ribs on outer ring, 1 rib on inner ring, type
NJ

X-life

Technical information



Your current product variant

Design	E	Increased Capacity Design
Cage	MPAX	One Piece Brass Cage Lip Guided
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (PN)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	150 mm	Bore diameter
D	270 mm	Outside diameter
B	45 mm	Width
C_r	520.000 N	Basic dynamic load rating, radial
C_{0r}	590.000 N	Basic static load rating, radial
C_{ur}	89.000 N	Fatigue load limit, radial
n_G	3.950 1/min	Limiting speed
n_{gr}	2.350 1/min	Reference speed
m	11,6 kg	Weight

Mounting dimensions

$d_{a \max}$	179 mm	Maximum diameter of shaft shoulder
$D_{a \max}$	256 mm	Maximum diameter of housing shoulder



Dimensions

r_{\min}	3 mm	Minimum chamfer dimension
$r_{1 \min}$	3 mm	Minimum chamfer dimension
s	4 mm	Axial displacement
E	242 mm	Raceway diameter outer ring
F	182 mm	Raceway diameter inner ring
$D_{1 \min}$	193,1 mm	Minimum rib diameter outer ring
d_1	233,2 mm	Maximum rib diameter inner ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed