

**FAG****6232-M-J20C-C3**

Deep groove ball bearing

Deep groove ball bearing 62...-M-J20C, single row, solid brass cage, ceramic coated

Technical information



Your current product variant

Sealing	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical
Coating	J20C	Current insulation, inner ring ceramic coated

Main Dimensions & Performance Data

d	160 mm	Bore diameter
D	290 mm	Outside diameter
B	48 mm	Width
C _r	212.000 N	Basic dynamic load rating, radial
C _{0r}	203.000 N	Basic static load rating, radial
C _{ur}	9.100 N	Fatigue load limit, radial
n _G	4.050 1/min	Limiting speed
n _{gr}	3.100 1/min	Reference speed
≈m	14,5 kg	Weight



Mounting dimensions

$d_{a \min}$	174 mm	Minimum diameter shaft shoulder
$D_{a \max}$	276 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum fillet radius

Dimensions

r_{\min}	3 mm	Minimum chamfer dimension
D_1	244,95 mm	Shoulder diameter outer ring
d_1	204,45 mm	Shoulder diameter inner ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Calculation factors

f_0	15,2	Calculation factor
-------	------	--------------------

Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Current insulated