



FAG

### **BND3056-H-W-Y-BF-D**

Housing body

For bearings with a conical bore and clamping sleeve with constant diameter, BND

## Technical information

### Main Dimensions & Performance Data



d 1	260 mm	Shaft diameter
a	760 mm	Length base
h 1	520 mm	Total height
g 1	236 mm	Total width with lid g1
g 2	281 mm	Total width with lid g2
≈m	163,7 kg	Weight



### Dimensions

b	240 mm	Width base
c	80 mm	Height base foot
D	420 mm	Outside Diameter
g	135 mm	Width housing body
g <sub>3</sub>	118 mm	Locking collar width g <sub>3</sub>
g <sub>4</sub>	108 mm	Locking collar width g <sub>4</sub>
h	260 mm	Distance shaft axis
k	4 mm	Axial displacement
m	630 mm	Distance fixing bore
n	140 mm	Bore distance width
s	M36	Size of fixing screws
s <sub>2</sub>	M16	Thread fixing bore
s <sub>2</sub>	8	Number of screwing holes
t	460 mm	Pitch circle dia fixing holes
u	42 mm	Width oblong holes
v	52 mm	Lenght oblong hole

### Additional information

H3056(-HG)	Adaptive Sleeve
23056..-K	Bearing designation

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.



View product details on medias

08.05.2026, 20:23:17 UTC

SCHAEFFLER

