


**MHA395-0-7-3-4-N-1530-01,0M-8-1-A** [↗](#)

sensing head

Measuring heads, for radial screw mounting

## Technical information

**Your current product variant**

Cable length 1 m

**Digital Output**

|    | Fanuc Serial # | Electronic interface |
|----|----------------|----------------------|
| ≈m | 133,77 g       | Weight               |

**Main Dimensions & Performance Data**

|                |        |                             |
|----------------|--------|-----------------------------|
| D              | 525 mm | Diameter bearing outer ring |
| H <sub>M</sub> | 54 mm  | Height                      |

**Mounting dimensions**

|                |          |  |
|----------------|----------|--|
| J <sub>M</sub> | 34 mm    | Bore distance                          |
| T              | 275,7 mm | Distance bearing center measuring head |

**Additional information**

|                      |                                   |
|----------------------|-----------------------------------|
| 5 Nm                 | Tightening torque                 |
| 0,5 Nm               | Tightening torque upper tolerance |
| -0,5 Nm              | Tightening torque lower tolerance |
| 2x ISO4762-M6x20-8.8 | Cylinder head screws              |



View product details on medias

23.06.2026, 01:34:59 UTC

SCHAEFFLER

### Cable

|       |                       |
|-------|-----------------------|
| M12x1 | Thread plug connector |
| 8     | Pins plug connector   |