



[View product details on medias](#)

07.07.2026, 09:47:21 UTC

**SCHAEFFLER**



## **ARCALUB-C4-2P-24VDC** [↗](#)

Automatic lubricator CONCEPT

CONCEPT4, Multi-point lubricator

### Technical information

---



Your current product variant

Drive System	PP	Piston pump
Lubricant volume	V400	400 cm <sup>3</sup>

Technical data

	Piston pump	Functional principle
V <sub>Lub</sub>	400 cm <sup>3</sup>	Lubricant volume
	0,16 cm <sup>3</sup>	Metering quantity (per outlet and stroke/impulse)
P <sub>op</sub>	70 bar	Operating pressure, max.
	≤ NLGI 3 (suitability test required)	Lubricant
n <sub>pb</sub>	2	Number of pump bodies
n <sub>out</sub>	4	Number of outlets
	≤ 4	Number of lubrication points: direct
	≤ 8	Number of lubrication points: with splitters
	> 12	Number of lubrication points: with progressive distributors
	PA hose	Connection
U <sub>op</sub>	DC 24 V	Operating voltage
	M12 x 1, 4 pin	Connection plug for multi-function interface
I <sub>max</sub>	≤ 350 mA	Current consumption (DC 24 V)
	PLC	Controller (extern)
	Integrated, electronic	Monitoring: pressure
	IP54	Protection class
	Polyamide	Housing material
t <sub>min</sub>	-15 °C	Operating temperature, min.
t <sub>max</sub>	60 °C	Operating temperature, max.
	vertical	Mounting position
	108,5 x 198,4 x 110,8	Dimensions (mm)
≈m	1,5 kg	Weight

