



[View product details on medias](#)

16.05.2026, 23:42:25 UTC

SCHAEFFLER



ARCALUB-C4-2P-24VDC [↗](#)

Automatic lubricator CONCEPT

CONCEPT4, Multi-point lubricator

Technical information



Your current product variant

Drive System	PP	Piston pump
Lubricant volume	V400	400 cm ³

Technical data

	Piston pump	Functional principle
V _{Lub}	400 cm ³	Lubricant volume
	0,16 cm ³	Metering quantity (per outlet and stroke/impulse)
P _{op}	70 bar	Operating pressure, max.
	≤ NLGI 3 (suitability test required)	Lubricant
n _{pb}	2	Number of pump bodies
n _{out}	4	Number of outlets
	≤ 4	Number of lubrication points: direct
	≤ 8	Number of lubrication points: with splitters
	> 12	Number of lubrication points: with progressive distributors
	PA hose	Connection
U _{op}	DC 24 V	Operating voltage
	M12 x 1, 4 pin	Connection plug for multi-function interface
I _{max}	≤ 350 mA	Current consumption (DC 24 V)
	PLC	Controller (extern)
	Integrated, electronic	Monitoring: pressure
	IP54	Protection class
	Polyamide	Housing material
t _{min}	-15 °C	Operating temperature, min.
t _{max}	60 °C	Operating temperature, max.
	vertical	Mounting position
	108,5 x 198,4 x 110,8	Dimensions (mm)
≈m	1,5 kg	Weight

