

**ARCALUB-C1-125-FOOD-OIL** [↗](#)

Automatic lubricator CONCEPT

CONCEPT1, Single-point lubricator (125 cm<sup>3</sup>, oil)

## Technical information

**Your current product variant**

|                  |      |                               |
|------------------|------|-------------------------------|
| Drive System     | HG   | Hydrogen gas development cell |
| Lubricant volume | V125 | 125 cm <sup>3</sup>           |

**Technical data**

|                  |                               |                                      |
|------------------|-------------------------------|--------------------------------------|
|                  | Gas drive                     | Functional principle                 |
| V <sub>Lub</sub> | 125 cm <sup>3</sup>           | Lubricant volume                     |
| P <sub>op</sub>  | 5 bar                         | Operating pressure, max.             |
|                  | ARCANOL-FOOD-OIL              | Lubricant                            |
| n <sub>out</sub> | 1                             | Number of outlets                    |
|                  | 1                             | Number of lubrication points: direct |
| U <sub>op</sub>  | —                             | Operating voltage                    |
|                  | IP68                          | Protection class                     |
|                  | Polyethylenterephthalat (PET) | Housing material                     |
| t <sub>min</sub> | -20 °C                        | Operating temperature, min.          |
| t <sub>max</sub> | 55 °C                         | Operating temperature, max.          |
|                  | arbitrary                     | Mounting position                    |
|                  | G $\frac{1}{4}$               | Connection thread                    |
|                  | 117,5 x 53 x 53               | Dimensions (mm)                      |
| ≈m               | 196 g                         | Weight                               |