

**FAG****1222-K-M**

Self-aligning ball bearing

Self-aligning ball bearing 12..-K-M, tapered bore taper 1:12, solid brass cage

Technical information



Your current product variant

Bore type	K	Tapered, taper 1:12
Type of Sealing	Without	Not sealed
Cage	M	Solid brass cage, ball guided
Tolerance class	PN	Tolerance class PN, acc. to DIN 620
Radial internal clearance	CN (Group N)	Normal internal clearance
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	110 mm	Bore diameter
D	200 mm	Outside diameter
B	38 mm	Width
C_r	89.000 N	Basic dynamic load rating, radial
C_{0r}	38.500 N	Basic static load rating, radial
C_{ur}	1.960 N	Fatigue load limit, radial
n_G	5.300 1/min	Limiting speed
n_{gr}	4.200 1/min	Reference speed
$\approx m$	5,27 kg	Weight



Mounting dimensions

$d_{a \min}$	122 mm	Minimum diameter shaft shoulder
$d_{a \max}$	138 mm	Maximum diameter shaft shoulder
$D_{a \max}$	188 mm	Maximum diameter of housing shoulder
$d_{b \min}$	116 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	7 mm	Minimum cavity width of the sleeve
$r_{a \max}$	2,1 mm	Maximum fillet radius

Dimensions

r_{\min}	2,1 mm	Minimum chamfer dimension
D_1	173,18 mm	Shoulder diameter outer ring
d_1	140,2 mm	Shoulder diameter inner ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Calculation factors

e	0,17	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	3,63	Dynamic axial load factor
Y_2	5,62	Dynamic axial load factor
Y_0	3,8	Static axial load factor

Additional information

H222

Adapter sleeve



Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment