


## Technical information



### Your current product variant

Cage	Standard	Polyamide cage
Sealing	2Z	Minimal gap seal on both sides
Arrangement bearing set	SU	Single bearing
Lubricant	Without	Not greased



### Main Dimensions & Performance Data

d	15 mm	Bore diameter
	0 mm	Bore diameter upper tolerance
	-0,004 mm	Bore diameter lower tolerance
D	47 mm	Outside diameter
	0 mm	Outside diameter upper tolerance
	-0,006 mm	Outside diameter lower tolerance
B	15 mm	Width
	0 mm	Width upper tolerance
	-0,12 mm	Width lower tolerance
C <sub>a</sub>	28.500 N	Basic dynamic load rating, axial
C <sub>0a</sub>	47.000 N	Basic static load rating, axial
C <sub>ua</sub>	2.850 N	Fatigue load limit, axial
n <sub>G</sub> Grease	8.700 1/min	Limiting speed for grease lubrication
n <sub>g</sub>	6.200 1/min	Thermally safe operating speed
≈m	0,14 kg	Weight

### Mounting dimensions

D <sub>a</sub>	43 mm	Diameter of housing
D <sub>a</sub>	H12	Diameter of housing clearance
d <sub>a</sub>	27 mm	Diameter shaft
d <sub>a</sub>	h12	Diameter shaft clearance

### Dimensions

r <sub>min</sub>	1 mm	Minimum chamfer dimension
r <sub>1 min</sub>	0,6 mm	Minimum chamfer dimension
a	29,9 mm	Distance between the apexes of the pressure cones
α	60 °	Contact angle








### Temperature range

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	120 °C	Operating temperature max.

### Additional information

$M_R$	0,08 Nm	Bearing frictional torque
$c_{aL}$	764 N/μm	Rigidity axial
	2 μm	Axial runout
	ZM17	Recommended INA precision locknut for radial locking
	AM17	Recommended INA precision locknut for axial locking
$M_A$	15 Nm	Tightening torque for the recommended INA precision locknut
	9.000 N	Required locknut force axial

### Characteristics

-  Radial load
-  Axial load in one direction
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides