

**FAG****6004-C-Z>V**

Deep groove ball bearing

Deep groove ball bearing 60.-C-Z, single row, Generation C, shield, steel sheet metal cage

## Technical information



## Your current product variant

|                                  |              |   |
|----------------------------------|--------------|---|
| Version code                     | >V           | Not marked on bearing                   |
| Changed internal design          | C            | GenerationC                             |
| Sealing                          | Z            | Non-contact shield on one Side          |
| Cage                             | JN           | Steel sheet metal                       |
| Tolerance class                  | P6           | Class 6 (ISO 492:2023)                  |
| Dimensional / heat stabilization | SN           | Rings dimensional stabilized up to 120° |
| Lubricant                        | Without      | Bearing not greased                     |
| Radial internal clearance        | CN (Group N) | Normal internal clearance               |
| Bore type                        | Z            | Cylindrical                             |

## Main Dimensions &amp; Performance Data

|                 |              |                                   |
|-----------------|--------------|-----------------------------------|
| d               | 20 mm        | Bore diameter                     |
| D               | 42 mm        | Outside diameter                  |
| B               | 12 mm        | Width                             |
| C <sub>r</sub>  | 10.600 N     | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 5.000 N      | Basic static load rating, radial  |
| C <sub>ur</sub> | 340 N        | Fatigue load limit, radial        |
| n <sub>G</sub>  | 27.500 1/min | Limiting speed                    |
| n <sub>gr</sub> | 19.700 1/min | Reference speed                   |
| ≈m              | 0,063 kg     | Weight                            |



### Mounting dimensions

|              |         |                                      |
|--------------|---------|--------------------------------------|
| $d_{a \min}$ | 23,2 mm | Minimum diameter shaft shoulder      |
| $D_{a \max}$ | 38,8 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 0,6 mm  | Maximum fillet radius                |

### Dimensions

|            |          |                              |
|------------|----------|------------------------------|
| $r_{\min}$ | 0,6 mm   | Minimum chamfer dimension    |
| $D_1$      | 35,45 mm | Shoulder diameter outer ring |
| $D_2$      | 37,38 mm | Caliber diameter outer ring  |
| $d_1$      | 26,55 mm | Shoulder diameter inner ring |
| $d_2$      | 25,38 mm | Caliber diameter inner ring  |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

### Calculation factors

|       |      |                    |
|-------|------|--------------------|
| $f_0$ | 13,8 | Calculation factor |
|-------|------|--------------------|

### Characteristics

|   |                              |
|---|------------------------------|
|  | Radial load                  |
|  | Axial load in one direction  |
|  | Axial load in two directions |
|  | Grease Lubrication           |
|  | Oil Lubrication              |
|  | Sealed on one side           |