


**RNAO35X45X26-ZW-ASR1-XL** [↗](#)

Needle roller bearing

Needle roller bearings RNAO...-ZW-ASR1,
without ribs, double row

X-life

Technical information



Your current product variant

Lubrication hole	ASR1	ASR1
Number of rolling element rows	ZW	Double-row design

Main Dimensions & Performance Data

F_w	35 mm	Under roller diameter
D	45 mm	Outside diameter
C	26 mm	Width, outer ring
C_r	31.500 N	Basic dynamic load rating, radial
C_{0r}	56.000 N	Basic static load rating, radial
C_{ur}	9.100 N	Fatigue load limit, radial
n_G	13.100 1/min	Limiting speed
n_{gr}	7.800 1/min	Reference speed
m	0,091 kg	Weight

Mounting dimensions

D_b	35,6 mm	Shoulder diameter axial guidance NK/housing
d_b	39,4 mm	Shoulder diameter axial guidance NK/shaft
D_a	40,5 mm	Shoulder diameter outer ring
$r_{a \max}$	0,3 mm	Maximum recess radius



Dimensions

E	40 mm	Raceway diameter outer ring
r _{min}	0,3 mm	Minimum chamfer dimension

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Small design envelope