



FAG

**QJ1016-XL-MPA**

Four-point contact bearing

Four point contact ball bearing QJ10...-XL-MPA, X-life, solid brass cage

X-life

## Technical information



## Your current product variant

Tolerance class	PN	Normal (ISO 492:2023)
Cage	MPA	Solid brass cage, outer ring guided
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Axial internal clearance	CN	Group N (CN)

## Main Dimensions &amp; Performance Data

d	80 mm	Bore diameter
D	125 mm	Outside diameter
B	22 mm	Width
C <sub>r</sub>	85.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	91.000 N	Basic static load rating, radial
C <sub>ur</sub>	6.300 N	Fatigue load limit, radial
n <sub>G</sub>	10.600 1/min	Limiting speed
n <sub>gr</sub>	4.500 1/min	Reference speed
m	1,07 kg	Weight

## Mounting dimensions

d <sub>a min</sub>	86 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	119 mm	Maximum diameter of housing shoulder
r <sub>a max</sub>	1 mm	Maximum fillet radius



### Dimensions

$r_{\min}$	1,1 mm	Minimum chamfer dimension
$D_1$	109,8 mm	Shoulder diameter outer ring
$d_1$	95,8 mm	Shoulder diameter inner ring
$a$	71,8 mm	Distance between the apexes of the pressure cones
$\alpha$	35 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

### Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed