





## PCJTZA40-XL

Flanged housing unit

X-life

### Technical information



### Your current product variant

Material	GG	Grey cast iron
----------	----	----------------

### Main Dimensions & Performance Data

d	40 mm	Bore diameter
L	111 mm	Flange width
H	180 mm	Height flange
U	46 mm	Total height unit
C <sub>r</sub>	32.500 N	Basic dynamic load rating, radial
C <sub>0r</sub>	20.400 N	Basic static load rating, radial
≈m	1,83 kg	Weight

### Mounting dimensions

J	148,5 mm	Distance fixing bore
N	14 mm	Fixing bore
T <sub>1</sub>	4 mm	Height spigot
Z	105 mm	Diameter spigot
	h8	Diameter spigot clearance
n	2	Number of screwing holes



### Dimensions

A	31 mm	Height housing
A <sub>1</sub>	13 mm	Thickness of flange
A <sub>2</sub>	20 mm	Distance raceway
B	33 mm	Width
V	111 mm	Shoulder diameter housing
Q	M6	Connection thread for lubrication

### Additional information

1	Number of housings
GEHCJTZ09-GG	Housing
GSPH209-NPP-B	Bearing designation

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.