

**RCJO100-XL**

## Flanged housing unit

Housing units RCJO, four-bolt flanged housing units, cast iron, eccentric locking collar, series 63, R seals

X-life

## Technical information



## Your current product variant

Material	GG	Grey cast iron
----------	----	----------------

## Main Dimensions &amp; Performance Data

d	100 mm	Bore diameter
L	310 mm	Flange width
U	125 mm	Total height unit
C <sub>r</sub>	184.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	141.000 N	Basic static load rating, radial
C <sub>ur</sub>	5.800 N	Fatigue load limit, radial
≈m	32,56 kg	Weight

## Mounting dimensions

J	242 mm	Distance fixing bore
N	32 mm	Fixing bore
n	4	Number of screwing holes



### Dimensions

A	97 mm	Height housing
A <sub>1</sub>	32 mm	Thickness of flange
A <sub>2</sub>	55 mm	Distance raceway
V	268 mm	Shoulder diameter housing
Q	M6	Connection thread for lubrication
d <sub>3</sub>	145 mm	Outside diameter locking device

### Additional information

1	Number of housings
GEHCJO20-GG	Housing
GEN100-XL-KRR-B	Bearing designation

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.