

**SL192324-TB-XL-BR**

## Cylindrical roller bearing

Cylindrical roller bearing SL1923, full compl, roller set self-retaining, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type SL19

## Technical information



## Your current product variant

Number of rows	1	Single-row design
----------------	---	-------------------

## Main Dimensions &amp; Performance Data

d	120 mm	Bore diameter
D	260 mm	Outside diameter
B	86 mm	Width
C <sub>r</sub>	1.130.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	1.230.000 N	Basic static load rating, radial
C <sub>ur</sub>	203.000 N	Fatigue load limit, radial
n <sub>G</sub>	1.940 1/min	Limiting speed
n <sub>gr</sub>	1.120 1/min	Reference speed
m	22,3 kg	Weight







## Dimensions

$D_1$	213,1 mm	Shoulder diameter outer ring
$D_{a \max}$	213 mm	Maximum diameter of housing shoulder
$d_1$	164,2 mm	Shoulder diameter inner ring
$d_{a \min}$	147 mm	Minimum diameter shaft shoulder
$d_{c \min}$	164 mm	Minimum shaft shoulder
F	147,4 mm	Raceway diameter inner ring
$r_{a \max}$	3 mm	Maximum fillet radius
$r_{\min}$	3 mm	Minimum chamfer dimension
s	5 mm	Axial displacement

## Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

## Characteristics

-   $F_r$  Radial load
-   $F_a$  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed