

**FAG****6001-C-Z>V**

## Deep groove ball bearing

Deep groove ball bearing 60...-C-Z, single row, Generation C, shield, steel sheet metal cage

## Technical information



## Your current product variant

Version code	>V	Not marked on bearing
Changed internal design	C	GenerationC
Sealing	Z	Non-contact shield on one Side
Cage	JN	Steel sheet metal
Tolerance class	P6	Class6 (P6), better then PN
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	12 mm	Bore diameter
D	28 mm	Outside diameter
B	8 mm	Width
C <sub>r</sub>	5.900 N	Basic dynamic load rating, radial
C <sub>0r</sub>	2.370 N	Basic static load rating, radial
C <sub>ur</sub>	164 N	Fatigue load limit, radial
n <sub>G</sub>	42.500 1/min	Limiting speed
n <sub>gr</sub>	26.000 1/min	Reference speed
≈m	0,019 kg	Weight



### Mounting dimensions

$d_{a \min}$	14 mm	Minimum diameter shaft shoulder
$D_{a \max}$	26 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,3 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	0,3 mm	Minimum chamfer dimension
$D_1$	23,34 mm	Shoulder diameter outer ring
$D_2$	25,1 mm	Caliber diameter outer ring
$d_1$	16,66 mm	Shoulder diameter inner ring
$d_2$	15,69 mm	Caliber diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Calculation factors

$f_0$	13,1	Calculation factor
-------	------	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Sealed on one side