

**KWVE45-B-SL**

Recirculating ball bearing carriage

Carriages KWVE...-B-SL, narrow, long carriage, four-row



Technical information

Your current product variant

Size code	45	
Version	B	
Carriage design	SL	Narrow, long carriage





Main Dimensions & Performance Data

H	60 mm	Height system
B	86 mm	Width carriage
L	172,7 mm	Overall length carriage
C	82.000 N	Dynamic load rating
C ₀	181.000 N	Static load rating
M _{0x}	4.635 Nm	Static moment rating about X axis
M _{0y}	4.000 Nm	Static moment rating about Y axis
M _{0z}	4.000 Nm	Static moment rating about Z axis
≈m	3,38 kg	Weight





Mounting dimensions



A ₁	20,5 mm	Distance from locating edge on carriage to locating edge on guideway
J _B	60 mm	
b	45 mm	Width rail
A ₂	13 mm	Distance from locating edge to hole
L ₁	134,6 mm	
L _S	2,2 mm	
J _L	80 mm	
H ₁	9,7 mm	Free space, system dimension
H ₅	9,25 mm	
T ₅	17 mm	Thread depth
G ₂	M10	Fixing screws above (DIN ISO 4762-12.9)
G _{2 M_A}	83 Nm	Maximum tightening torque
A ₃	16,5 mm	Position lubrication connector
G ₃	M6	Lubrication connector
t _{G₃}	7 mm	Maximum permissible screw depth for lubrication connectors
A ₄	16,5 mm	Position lubrication connector
G ₄	M6	Lubrication connector
t _{G₄}	7 mm	Maximum permissible screw depth for lubrication connectors
J _{L6}	35,3 mm	Position lubrication connector

Additional information

VMKB_065	KWVE	Material name
----------	------	---------------