


**GYE30-XL-KRR-B-AS2/V**

Radial insert ball bearing

Radial insert ball bearings GYE...-KRR-B, spherical outer ring, location by grub screws, R seals on both sides

X-life

## Technical information



## Your current product variant

Lubrication hole transposed AS2/V

## Main Dimensions &amp; Performance Data

d	30 mm	Bore diameter
D <sub>SP</sub>	62 mm	Outside diameter
B	38,1 mm	Width
C <sub>0r</sub>	11.300 N	Basic static load rating, radial
C <sub>ur</sub>	480 N	Fatigue load limit, radial
C <sub>r</sub>	19.500 N	Basic dynamic load rating, radial
≈m	0,294 kg	Weight

## Dimensions

C	18 mm	Width, outer ring
C <sub>2</sub>	19,8 mm	Sealing total width
S	15,9 mm	Distance raceway
d <sub>1</sub>	40,2 mm	Rib diameter inner ring
D <sub>1</sub>	52 mm	Outside diameter seal
C <sub>a</sub>	5 mm	Distance to lubrication hole
A	5,8 mm	Distance thread
W	3 mm	Width of flats








### Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

### Calculation factors

$f_0$	13,8	Calculation factor
-------	------	--------------------

### Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides
-  Static angular error and misalignment