

IMAGE  
COMING SOON**GE50-XL-KRR-B-AS2/V-2C-OSE**

Radial insert ball bearing

## Technical information

**Your current product variant**

Lubrication hole transposed	AS2/V	
Flinger shields	2C	Flinger shield on both sides

**Main Dimensions & Performance Data**

d	50 mm	Bore diameter
D <sub>SP</sub>	90 mm	Outside diameter
B	49,2 mm	Width
C <sub>0r</sub>	23.200 N	Basic static load rating, radial
C <sub>ur</sub>	1.210 N	Fatigue load limit, radial
C <sub>r</sub>	37.500 N	Basic dynamic load rating, radial
m	0,771 kg	Weight

**Dimensions**

C	22 mm	Width, outer ring
C <sub>2</sub>	35,4 mm	Sealing total width
d <sub>1</sub>	62,8 mm	Rib diameter inner ring
C <sub>a</sub>	6,9 mm	Distance to lubrication hole

**Temperature range**

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.



### Calculation factors

---

$f_0$	14,4	Calculation factor
-------	------	--------------------

### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides
-  Static angular error and misalignment