

IMAGE
COMING SOON**GE50-XL-KRR-B-AS2/V-2C**

Radial insert ball bearing

Technical information

Your current product variant

Lubrication hole transposed	AS2/V	
Flinger shields	2C	Flinger shield on both sides

Main Dimensions & Performance Data

d	50 mm	Bore diameter
D _{SP}	90 mm	Outside diameter
B	49,2 mm	Width
C _{0r}	23.200 N	Basic static load rating, radial
C _{ur}	1.210 N	Fatigue load limit, radial
B ₁	62,8 mm	Locking collar total width
C _r	37.500 N	Basic dynamic load rating, radial
m	0,981 kg	Weight

Dimensions

C	22 mm	Width, outer ring
C ₂	35,4 mm	Sealing total width
S	24,6 mm	Distance raceway
d ₁	62,8 mm	Rib diameter inner ring
C _a	6,9 mm	Distance to lubrication hole
d ₃	69 mm	Outside diameter locking collar/locknut
W	5 mm	Width of flats










Temperature range

T_{min}	-20 °C	Operating temperature min.
T_{max}	100 °C	Operating temperature max.

Calculation factors

f_0	14,4	Calculation factor
-------	------	--------------------

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides
-  Static angular error and misalignment