

**FAG****HC6206-C-2HRS-TVH-L207-C3>V**

Deep groove ball bearing

Deep groove ball bearing HC62...-C-2HRS-TVH, Hybrid bearing, single row, Generation C, seals, plastic cage

Technical information



Your current product variant

Version code	>V	Not marked on bearing
Material Bearing	HC	Hybrid bearing, rolling elements ceramic, bearing rings made of steel
Changed internal design	C	GenerationC
Type of Seal	2HRS	Contact seal on both sides
Cage	TVH	Solid cage made of glass-fiber reinforced polyamid PA66
Tolerance class	P6	Class6 (P6), better then PN
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	L207	Low noise high-temperature grease, interchangeable with grease L069
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical



Main Dimensions & Performance Data

d	30 mm	Bore diameter
D	62 mm	Outside diameter
B	16 mm	Width
C _r	22.000 N	Basic dynamic load rating, radial
C _{0r}	10.800 N	Basic static load rating, radial
C _{ur}	560 N	Fatigue load limit, radial
n _G	10.200 1/min	Limiting speed
≈m	0,167 kg	Weight

Mounting dimensions

d _{a min}	35,6 mm	Minimum diameter shaft shoulder
D _{a max}	56,4 mm	Maximum diameter of housing shoulder
r _{a max}	1 mm	Maximum fillet radius

Dimensions

r _{min}	1 mm	Minimum chamfer dimension
D ₁	52,67 mm	Shoulder diameter outer ring
D ₂	54,92 mm	Caliber diameter outer ring
d ₁	39,33 mm	Shoulder diameter inner ring
d ₂	37,72 mm	Caliber diameter inner ring

Temperature range








T _{min}	-30 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.

Calculation factors

f ₀	13,2	Calculation factor
----------------	------	--------------------



Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides
-  Current insulated