

**FAG****6200-C-Z-HRS-L069-C3>V**

Deep groove ball bearing

Deep groove ball bearing 62...-C-Z-HRS, single row, Generation C, shield/seal, steel sheet metal cage

Technical information



Your current product variant

| | | |
|----------------------------------|--------------|---|
| Version code | >V | Not marked on bearing |
| Changed internal design | C | GenerationC |
| Type of Seal | Z-HRS | Non-contact shield on one Side, Contact seal on the other side |
| Cage | JN | Steel sheet metal |
| Tolerance class | P6 | Class6 (P6), better then PN |
| Dimensional / heat stabilization | SN | Rings dimensional stabilized up to 120° |
| Lubricant | L069 | Low noise high-temperature grease, interchangeable with grease L207 |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Bore type | Z | Cylindrical |

Main Dimensions & Performance Data

| | | |
|-----------------|--------------|-----------------------------------|
| d | 10 mm | Bore diameter |
| D | 30 mm | Outside diameter |
| B | 9 mm | Width |
| C _r | 7.000 N | Basic dynamic load rating, radial |
| C _{0r} | 2.600 N | Basic static load rating, radial |
| C _{ur} | 181 N | Fatigue load limit, radial |
| n _G | 26.000 1/min | Limiting speed |
| m | 0,03 kg | Weight |



Mounting dimensions

| | | |
|--------------|---------|--------------------------------------|
| $d_{a \min}$ | 14,2 mm | Minimum diameter shaft shoulder |
| $D_{a \max}$ | 25,8 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 0,6 mm | Maximum fillet radius |

Dimensions

| | | |
|------------|----------|------------------------------|
| r_{\min} | 0,6 mm | Minimum chamfer dimension |
| D_1 | 23,89 mm | Shoulder diameter outer ring |
| D_2 | 25,64 mm | Caliber diameter outer ring |
| d_1 | 16,11 mm | Shoulder diameter inner ring |
| d_2 | 15,14 mm | Caliber diameter inner ring |






Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 100 °C | Operating temperature max. |

Calculation factors

| | | |
|-------|----|--------------------|
| f_0 | 12 | Calculation factor |
|-------|----|--------------------|

Characteristics

| | |
|---|------------------------------|
|  | Radial load |
|  | Axial load in one direction |
|  | Axial load in two directions |
|  | Grease Lubrication |
|  | Sealed on both sides |