



## HEATER1600-BASIC-400V [↗](#)

Induction heating device

HEATER basic

### Technical information



#### Your current product variant

Series	BASIC	Base version
--------	-------	--------------

#### Technical data

U	400 V	Operating voltage
f	50 – 60 Hz	Power frequency
P	40 kVA	Power consumption
I	100 A	Current rating
$\vartheta_{h \text{ max}}$	240 °C	Max. heating temperature
	0 – 99 min	Heating time
	Digital	Display
	1	Magnetic probe, quantity
$\approx m$	920 kg	Weight



## Functions

+	Temperature hold
+	Automatic demagnetization, <2A/cm
—	Swivel arm
—	Log function
—	Delta-T control
+	Temperature control
+	Time control
—	Temperature and time control
—	Temperature and speed control
+	Overheating protection
+	Automatic power reduction
+	Device supports horizontal / lying heating of the workpiece
—	Device supports vertical / hanging heating of the workpiece

## Dimensions

	1.520 mm	Length HEATER
	750 mm	Width HEATER
	1.415 mm	Height HEATER
B	710 mm	Space between poles
C	780 mm	Pole length

## Workpiece to be heated

	215 mm	Min. inner diameter workpiece, horizontal heating: with included yoke
	85 mm	Min. inner diameter workpiece, horizontal heating: with optional yoke
ØA max	1.700 mm	Max. outer diameter workpiece
	700 mm	Max. workpiece width, horizontal heating
<sup>m</sup> b max	1.600 kg	Max. workpiece weight



View product details on medias

12.06.2026, 23:42:27 UTC

SCHAEFFLER

### Additional information

---

1	Yokes included, quantity
150x150	Yokes included, cross section (mm <sup>2</sup> )