

**FAG****51284-MP**

Axial deep groove ball bearing

Axial deep groove ball bearing 512...-MP,
single direction, solid brass cage

Technical information



Your current product variant

Cage	MP	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°

Main Dimensions & Performance Data

d	420 mm	Inner diameter shaft washer
D	580 mm	Outer diameter housing washer
T	130 mm	Height
C _a	870.000 N	Basic dynamic load rating, axial
C _{0a}	5.100.000 N	Basic static load rating, axial
C _{ua}	104.000 N	Fatigue load limit, axial
n _G	690 1/min	Limiting speed
n _{gr}	750 1/min	Reference speed
m	106 kg	Weight

Mounting dimensions

d _{a min}	516 mm	Minimum diameter shaft shoulder
D _{a max}	484 mm	Maximum diameter of housing shoulder
r _{a max}	4 mm	Maximum filled radius



Dimensions

r_{min}	5 mm	Minimum chamfer dimension
D_1	425 mm	Inner diameter housing washer
d_1	575 mm	Outer diameter shaft washer






Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	200 °C	Operating temperature max.

Calculation factors

A	141	Minimum load factor
---	-----	---------------------

Characteristics

-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing