


**LFS52-C**

## Guideway

hollow section profile, with two raceway shafts; corrosion-resistant design possible

## Technical information

**Your current product variant**

Size Code	52
Design	C Hollow section profile

**Main Dimensions & Performance Data**

h	34 mm	Height
b	52 mm	Width
l <sub>max</sub>	6.000 mm	Length maximum
I <sub>y</sub>	113.821 mm <sup>4</sup>	Second moment of area
I <sub>z</sub>	74.878 mm <sup>4</sup>	Second moment of area
LF <sub>Q</sub>	649 mm <sup>2</sup>	Cross-sectional area
W <sub>y</sub>	4.896 mm <sup>3</sup>	Wider resistance torque
W <sub>z</sub>	4.378 mm <sup>3</sup>	Wider resistance torque

**Mounting dimensions**

N <sub>1</sub>	11 mm	Bore diameter
N <sub>3</sub>	19 mm	Bore diameter



### Dimensions

a <sub>2</sub>	42 mm	Distance
a <sub>L max</sub>	235 mm	Distance
a <sub>L min</sub>	17 mm	Distance
a <sub>R max</sub>	235 mm	Distance
a <sub>R min</sub>	17 mm	Distance
b <sub>1</sub>	40 mm	Width
d <sub>LW</sub>	10 mm	Diameter
e <sub>Z</sub>	17,1 mm	Distance
h <sub>1</sub>	21 mm	Height
h <sub>4</sub>	25,1 mm	Height
j <sub>L</sub>	250 mm	Increment