

**FAG****2213-TVH>N**

Self-aligning ball bearing

Self-aligning ball bearing 22..-TVH, plastic cage

## Technical information



## Your current product variant

Version code	>N	Not marked on bearing
Bore type	Z	Cylindrical
Type of Sealing	Without	Not sealed
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	PN	Tolerance class PN, acc. to DIN 620
Radial internal clearance	CN (Group N)	Normal internal clearance
Lubricant	Without	Bearing not greased

## Main Dimensions &amp; Performance Data

d	65 mm	Bore diameter
D	120 mm	Outside diameter
B	31 mm	Width
$C_r$	58.000 N	Basic dynamic load rating, radial
$C_{0r}$	19.200 N	Basic static load rating, radial
$C_{ur}$	1.220 N	Fatigue load limit, radial
$n_G$	5.600 1/min	Limiting speed
$n_{gr}$	6.200 1/min	Reference speed
$m$	1,35 kg	Weight



### Mounting dimensions

$d_{a \min}$	74 mm	Minimum diameter shaft shoulder
$D_{a \max}$	111 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1,5 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	1,5 mm	Minimum chamfer dimension
$D_1$	106,88 mm	Shoulder diameter outer ring
$d_1$	82,4 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Calculation factors

$e$	0,23	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y_1$	2,78	Dynamic axial load factor
$Y_2$	4,3	Dynamic axial load factor
$Y_0$	2,91	Static axial load factor

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Static angular error and misalignment
	Dynamic angular error and misalignment