**LFS32-N**

## Guideway

solid profile, with T-slot, with two raceway shafts; corrosion-resistant design possible

## Technical information

## Your current product variant




Size Code	32	
Design	N	Solid profile, with T-slot

## Main Dimensions &amp; Performance Data

h	20 mm	Height
b	32 mm	Width
$l_{max}$	4.000 mm	Length maximum
$I_y$	19.600 mm <sup>4</sup>	Second moment of area
$I_z$	12.600 mm <sup>4</sup>	Second moment of area
LF <sub>Q</sub>	360 mm <sup>2</sup>	Cross-sectional area
W <sub>y</sub>	1.400 mm <sup>3</sup>	Wider resistance torque
W <sub>z</sub>	1.135 mm <sup>3</sup>	Wider resistance torque

## Mounting dimensions

N <sub>1</sub>	6 mm	Bore diameter
----------------	------	---------------





### Dimensions

a <sub>2</sub>	26 mm	Distance
b <sub>1</sub>	24 mm	Width
b <sub>3</sub>	6,5 mm	Width
b <sub>4</sub>	10,5 mm	Width
b <sub>5</sub>	10,5 mm	Width
d <sub>LW</sub>	6 mm	Diameter
e <sub>Z</sub>	11,1 mm	Distance
h <sub>1</sub>	4 mm	Height
h <sub>2</sub>	6 mm	Height
h <sub>4</sub>	15 mm	Height
j <sub>L</sub>	125 mm	Increment
t <sub>7</sub>	1,6 mm	Depth