



**RASEY40-TV-VA-FD**

Plummer block housing unit

Plummer block housing units, FD design

## Technical information



## Your current product variant

Special material	TV	Plastic housing
Corrosion resistant bearing	VA	Corrosion-resistant VA design
Material	TV-FD	Plastic for food industry

## Main Dimensions &amp; Performance Data

d	40 mm	Bore diameter
L	184 mm	Length
H <sub>2</sub>	98 mm	Height
≈m	0,98 kg	Weight

## Mounting dimensions

J	137 mm	Distance fixing bore
N	14 mm	Width (slot)
N <sub>1</sub>	18 mm	Length (slot)
W	4 mm	Width of flats



### Dimensions

H	49,2 mm	Distance shaft axis
A	54 mm	Width (base)
H <sub>1</sub>	19,5 mm	Height (base)
B	49,2 mm	Width
B <sub>3</sub>	51,5 mm	Distance housing centre to cap end
S <sub>1</sub>	30,2 mm	Distance raceway to locking collar
Q	1/4"-28 UNF	Connection thread for lubrication

### Additional information

GEH.ASE08-TV-WHT	Housing
GYE40-KRR-B-FA107-VA-FD	Bearing designation
KASK08-S-G-WHT	End cap
KASK08-S-R-NBR-WHT	Open protecting cap

### Temperature range

T <sub>min</sub>	-30 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.