

**RSHEY25-TV-VA-FD**

Plummer block housing unit

Plummer block housing units, FD design

Technical information

Your current product variant

Special material	TV	Plastic housing
Corrosion resistant bearing	VA	Corrosion-resistant VA design
Material	TV-FD	Plastic for food industry

Main Dimensions & Performance Data



d	25 mm	Bore diameter
L	76,2 mm	Length
H 2	73,5 mm	Height
≈m	0,37 kg	Weight

Mounting dimensions

J	50,8 mm	Distance fixing bore
K	M10	Thread fixing bore
W	2,5 mm	Width of flats

Dimensions

H	36,5 mm	Distance shaft axis
A	39,5 mm	Width (base)
B	34,1 mm	Width
B 3	35,05 mm	Distance housing centre to cap end
S 1	19,8 mm	Distance raceway to locking collar
Q	1/4"-28 UNF	Connection thread for lubrication





Additional information

GEH.SHE05-TV-WHT	Housing
GYE25-KRR-B-FA107-VA-FD	Bearing designation
KASK05-S-G-WHT	End cap
KASK05-S-R-NBR-WHT	Open protecting cap

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.