

**FAG****HC6305-C-2Z-L207-C3>V**

Deep groove ball bearing

Deep groove ball bearing HC63...-C-2Z,
Hybrid bearing, single row, Generation C,
shields, steel sheet metal cage

Technical information

**Your current product variant**

Version code	>V	Not marked on bearing
Material Bearing	HC	Hybrid bearing, rolling elements ceramic, bearing rings made of steel
Changed internal design	C	GenerationC
Type of Seal	2Z	Non-contact shield on both sides
Cage	JN	Steel sheet metal
Tolerance class	P6	Class6 (P6), better than PN
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	L207	Low noise high-temperature grease, interchangeable with grease L069
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical



Main Dimensions & Performance Data

d	25 mm	Bore diameter
D	62 mm	Outside diameter
B	17 mm	Width
C _r	26.500 N	Basic dynamic load rating, radial
C _{0r}	11.000 N	Basic static load rating, radial
C _{ur}	580 N	Fatigue load limit, radial
n _G	18.100 1/min	Limiting speed
n _{gr}	13.500 1/min	Reference speed
m	0,195 kg	Weight

Mounting dimensions

d _{a min}	32 mm	Minimum diameter shaft shoulder
D _{a max}	55 mm	Maximum diameter of housing shoulder
r _{a max}	1 mm	Maximum fillet radius

Dimensions

r _{min}	1,1 mm	Minimum chamfer dimension
D ₁	51,55 mm	Shoulder diameter outer ring
D ₂	53,8 mm	Caliber diameter outer ring
d ₁	35,45 mm	Shoulder diameter inner ring
d ₂	34,12 mm	Caliber diameter inner ring

Temperature range








T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Calculation factors

f ₀	11,9	Calculation factor
----------------	------	--------------------



Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides
-  Current insulated