



Dimensions

α	4 °	Tilt angle
C ₁	103 mm	Width of the rod end
C ₂	72 mm	Width
d _K	160 mm	Ball diameter
d ₃	M100x3	Thread size
d ₄	135 mm	Shank diameter
d ₅	200 mm	Shank diameter, large
d ₇	M24x70	Diameter screw clamp
h ₁	260 mm	Shank Length Internal thread head
l ₃	113 mm	Thread length Internal thread
l ₇	120 mm	Distance drilling with/shaft start
d _{UT}	0 mm	Bore diameter bearing, lower tolerance
d _T	H7	Bore diameter bearing, tolerance
d _{OT}	0,04 mm	Bore diameter bearing, upper tolerance
B _{UT}	-0,4 mm	Width inner ring, lower tolerance
B _{OT}	0 mm	Width inner ring, upper tolerance
M _A	660 Nm	Tightening torque
F _Z	800.000 N	Cylinder Force
G _r	CN	Radial Clearance
G _{rmin}	0,043 mm	Radial clearance, minimum
G _{rmax}	0,165 mm	Radial clearance, maximum

Mounting dimensions








r _{1smin}	1 mm	Edge Spacing
d ₁	138 mm	Outer flange diameter inner ring



Temperature range

T_{min}	-60 °C	Operating temperature min.
T_{max}	200 °C	Operating temperature max.

Characteristics

-  F_r Radial load
-  F_a Axial load in one direction
-  F_a Axial load in two directions
-  Grease Lubrication
-  Not sealed
-  Static angular error and misalignment
-  Dynamic angular error and misalignment