

**EGB1008-E40**

## Bush

Metal/polymer composite plain bush,  
maintenance-free, ISO 3547, with steel  
backing

## Technical information

**Your current product variant**

Maintenance	Maintenance free	
Type of Seal	Without	Not sealed
Material sliding Layer	E40	Maintenance-free sliding layer E40
Material back	Steel	

**Main Dimensions & Performance Data**

$D_i$	10 mm	Inner diameter
$D_o$	12 mm	Outer diameter
B	8 mm	Width
$C_r$	11.200 N	Basic dynamic load rating, radial
$C_{0r}$	20.000 N	Basic static load rating, radial
$\approx m$	1,85 g	Weight



## Dimensions

$f$	20 °	Chamfer angle outside diameter
$f$	0,6 mm	Outer chamfer
$F_{i\ min}$	0,1 mm	Inner edge break, min.
$F_{i\ max}$	0,6 mm	Inner edge break, max.
$D_{i\ OT}$	0,049 mm	Inner diameter, upper tolerance
$D_{o\ OT}$	0,065 mm	Outside diameter, upper tolerance
$D_{i\ UT}$	-0,001 mm	Inner diameter, lower tolerance
$D_{o\ UT}$	0,03 mm	Outside diameter, lower tolerance
$s_3$	1 mm	Wall thickness
$s_3\ OT$	0,005 mm	Wall thickness, upper tolerance
$s_3\ UT$	-0,02 mm	Wall thickness, lower tolerance
$B_{UT}$	-0,25 mm	Width, lower tolerance
$B_{OT}$	0,25 mm	Width, upper tolerance
$f_{OT}$	0,4 mm	Outer chamfer, upper tolerance
$f_{UT}$	-0,4 mm	Outer chamfer, lower tolerance
$F_i$	0,1 mm	Inner edge break

## Temperature range

$T_{min}$	-200 °C	Operating temperature min.
$T_{max}$	280 °C	Operating temperature max.

## Characteristics



Radial load



Lifetime lubrication, freedom from maintenance



Not sealed



Small design envelope