

**RSL185026-A-2S**

## Cylindrical roller bearing

Cylindrical roller bearing RSL18, full complement roller set, two-row, semi-locating bearing, no outer ring, 3 ribs on inner ring, type RSL18

## Technical information

**Your current product variant**

Design	A	Internal Variant Cage A
Number of rows	2	Double-row design

**Main Dimensions & Performance Data**

d	130 mm	Rib diameter inner ring
E <sub>w</sub>	183,81 mm	Outer envelope circle
B	95 mm	Width
C <sub>r</sub>	730.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	1.210.000 N	Basic static load rating, radial
C <sub>ur</sub>	167.000 N	Fatigue load limit, radial
n <sub>G</sub>	1.990 1/min	Limiting speed
n <sub>gr</sub>	1.340 1/min	Reference speed
≈m	6,597 kg	Weight

**Mounting dimensions**

d <sub>a min</sub>	149 mm	Minimum diameter shaft shoulder
--------------------	--------	---------------------------------

**Dimensions**

r <sub>min</sub>	2 mm	Minimum chamfer dimension
X	78 mm	Raceway width



### Temperature range

---


$T_{min}$  -30 °C Operating temperature min.

$T_{max}$  120 °C Operating temperature max.

### Characteristics

---

  $F_r$  Radial load

 Grease Lubrication

 Oil Lubrication

 Not sealed