

**RSL185026-A-2S**

Cylindrical roller bearing

Cylindrical roller bearing RSL18, full complement roller set, two-row, semi-locating bearing, no outer ring, 3 ribs on inner ring, type RSL18

Technical information

**Your current product variant**

Design	A	Internal Variant Cage A
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	130 mm	Rib diameter inner ring
E _w	183,81 mm	Outer envelope circle
B	95 mm	Width
C _r	730.000 N	Basic dynamic load rating, radial
C _{0r}	1.210.000 N	Basic static load rating, radial
C _{ur}	167.000 N	Fatigue load limit, radial
n _G	1.990 1/min	Limiting speed
n _{gr}	1.340 1/min	Reference speed
≈m	6,597 kg	Weight

Mounting dimensions

d _{a min}	149 mm	Minimum diameter shaft shoulder
--------------------	--------	---------------------------------

Dimensions

r _{min}	2 mm	Minimum chamfer dimension
X	78 mm	Raceway width



Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed