

**GE44-ZO-2RS-E**

Spherical plain bearing

Spherical plain bearing

Technical information



Your current product variant

Maintenance	Maintenance required
Material	Steel
Sealing	2RS Lip seals on both sides
Radial internal clearance	CN (Group N) Normal internal clearance
Coating	Durotect M Inner- and outer ring coated with Durotect M (Manganese Phosphate)

Main Dimensions & Performance Data

d	44,45 mm	Bore diameter bearing
D	71,438 mm	Outside diameter bearing
B	38,887 mm	Width inner ring
C_r	170.000 N	Basic dynamic load rating, radial
C_{0r}	852.000 N	Basic static load rating, radial
$\approx m$	0,62 kg	Weight

Mounting dimensions

$r_{1\text{min}}$	0,6 mm	Edge Spacing
$r_{2\text{min}}$	0,6 mm	Edge Spacing
$d_{a\text{max}}$	50,9 mm	Connection measure Inner ring
$D_{a\text{min}}$	57 mm	Housing Connection Diameter



Dimensions

C	33,325 mm	Width Outer ring
d _K	63,9 mm	Ball diameter
α	6 °	Tilt angle
d _{OT}	0 mm	Bore diameter bearing, upper tolerance
d _{UT}	-0,012 mm	Bore diameter bearing, lower tolerance
d _T	0,012	Bore diameter bearing, tolerance
D _{OT}	0 mm	Outside diameter, upper tolerance
D _{UT}	-0,013 mm	Outside diameter, lower tolerance
B _{OT}	0 mm	Width inner ring, upper tolerance
B _{UT}	0 mm	Width inner ring, lower tolerance
C _{OT}	0 mm	Width outer ring, upper tolerance
C _{UT}	-0,3 mm	Width outer ring, lower tolerance
G _r	0,1	Radial Clearance
G _{rmax}	0,18 mm	Radial clearance, maximum
G _{rmin}	0,08 mm	Radial clearance, minimum

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	130 °C	Operating temperature max.



Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Sealed on both sides



Static angular error and misalignment



Dynamic angular error and misalignment