



View product details on medias

16.06.2026, 21:46:56 UTC

SCHAEFFLER




OPTIME-LW-C1-R3 [↗](#)

Automatic lubrication system

OPTIME C1, Single-point lubricator for the OPTIME Ecosystem

Technical information



Technical data

	Piston pump	Functional principle
V _{Lub}	60 / 125 cm ³	Lubricant volume
	≈ 0,5 cm ³	Metering volume per lubrication interval
	0,17 – 8,3 cm ³	Metering volume per day
P _{op}	10 bar	Operating pressure, max.
	≤ NLGI 2 (suitability test required)	Lubricant
n _{out}	1	Number of outlets
	1	Number of lubrication points: direct
U _{op}	6-V alkaline battery	Operating voltage
	OPTIME	Controller (integrated)
	via OPTIME	Monitoring: fill level
	1 up to 12 months	Dispensing time cartridge
	Empty level, back pressure, internal error: via OPTIME	Error message
	NFC	Commissioning
	2,4 GHz	Wirepas Mesh (ISM band)
	100 m	Line of sight range
	IP68	Protection class
	Polyethylenerephthalat (PET)	Housing material
t _{min}	-10 °C	Operating temperature, min.
t _{max}	55 °C	Operating temperature, max.
	arbitrary	Mounting position
	G ¹ / ₄	Connection thread
	60 x 60 x 93	Dimensions (mm)
≈m	0,26 kg	Weight



Additional information

10x OPTIME C1, 10x battery pack, 1x OPTIME C1 prefill nipple; lubricant cartridge CONCEPT1 not included	Scope of delivery per package
---	-------------------------------

EU-Members, Israel, Republic of Macedonia, Norway, Morocco, Serbia, Saudi Arabia, United Arab Emirates, South Africa, Switzerland, Turkey, UK, Australia, China, India, Indonesia, South Korea, Taiwan, Japan, Malaysia, New Zealand, Philippines, Singapore, Thailand, Vietnam, Canada, Brazil, Colombia, Peru, Mexico, Chile, USA	Country approvals
---	-------------------