



**FAG****K1922**

## Outer ring

Tapered roller bearings without inner subunit  
(Cup) K-Series, in inch sizes

## Technical information



## Your current product variant

Tolerance class	ABMA4	Class 4 (ANSI/ABMA 19.2:2013)
Heat treatment	Standard	
Internal design	Standard	
Quality level	Standard	
Number of rows	1	Single-row design

## Main Dimensions &amp; Performance Data

D	57,15 mm	Outside diameter
C	15,875 mm	Width, outer ring
≈m	0,078 kg	Weight

## Mounting dimensions

D <sub>a</sub> min	51 mm	Minimum diameter of housing shoulder
D <sub>b</sub> min	53,5 mm	Minimum diameter of housing shoulder
r <sub>b</sub> max	1,5 mm	Maximum fillet radius of housing

## Dimensions



r <sub>3, 4</sub> min	1,5 mm	Minimum chamfer dimension of outer ring back face
E	46,13 mm	Inside diameter of outer ring back face
α	12,408 °	Contact angle



### Temperature range

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	120 °C	Operating temperature max.

### Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed