

**FAG****NJ2326-E-XL-MPAX-ILR**

Cylindrical roller bearing

Cylindrical roller bearing NJ..-E..-MPAX-ILR, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

Technical information



Your current product variant

Design	E	Increased Capacity Design
Cage	MPAX	One Piece Brass Cage Lip Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	130 mm	Bore diameter
D	280 mm	Outside diameter
B	93 mm	Width
C_r	1.340.000 N	Basic dynamic load rating, radial
C_{0r}	1.220.000 N	Basic static load rating, radial
C_{ur}	198.000 N	Fatigue load limit, radial
n_G	4.250 1/min	Limiting speed
n_{gr}	1.750 1/min	Reference speed
$\approx m$	29,2 kg	Weight

Mounting dimensions

$D_{a \max}$	266 mm	Maximum diameter of housing shoulder
--------------	--------	--------------------------------------






Dimensions

r_{\min}	4 mm	Minimum chamfer dimension
$r_{1\min}$	4 mm	Minimum chamfer dimension
s	8,2 mm	Axial displacement
E	247 mm	Raceway diameter outer ring
F	167 mm	Raceway diameter inner ring
$D_{1\min}$	235,2 mm	Minimum rib diameter outer ring
d_1	181,7 mm	Maximum rib diameter inner ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Large bearing